



40 mm x 68 mm x 9 mm NSK 54208 thrust ball bearings

Bearing No. 54208

54208 Bearing 2D drawings and 3D CAD models

Size	40x68x38.6 mm
Bore Diameter	40 mm
Outer Diameter	68 mm
Width	38,6 mm
d	40 mm
d2	30 mm
D	68 mm
T	38,6 mm
T2	23,8 mm
d3	68 mm
r min.	1 mm
r1 min.	0,6 mm
A1	25 mm
B	9 mm
D1	42 mm
R	56 mm
Da max.	55 mm
ra max.	1 mm
rb max.	0,6 mm
Weight	0,581 Kg
Basic dynamic load rating (C)	47,5 kN
Basic static load rating (C0)	98,5 kN
(Grease) Lubrication Speed	2600 r/min
Category	Thrust Ball Bearing
Inventory	0.0



Timken MANUFACTURING (THAILAND)CO.,LTD.

Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.7
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row With Aligning Seat
Long Description	30MM Bore 1; 42MM Bore 2; 68MM Outside Diameter; 38.6MM Height; Ball Bearing; Double Direction; Not Banded; Steel Cage; Non-Precision
Inch - Metric	Metric
Category	Thrust Ball Bearings
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer URL	http://www.nskamericas.com
Weight / LBS	1.19711
Height	1.52 Inch 38.6 Millimeter
Bore 2	1.654 Inch 42 Millimeter
Bore 1	1.181 Inch 30 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	2.677 Inch 68 Millimeter



Timken MANUFACTURING (THAILAND)CO.,LTD.