



**38,1 mm x 95,25 mm x 28,301 mm NSK
53150/53375 tapered roller bearings**

Bearing No. 53150/53375

53150/53375 Bearing 2D drawings and 3D CAD models

Size	38.1x95.25x30.958 mm
Bore Diameter	38,1 mm
Outer Diameter	95,25 mm
Width	30,958 mm
d	38,1 mm
D	95,25 mm
T	30,958 mm
B	28,301 mm
C	20,638 mm
ra1 max.	0,8 mm
a	30,7 mm
r min.	1,5 mm
r1 min.	0,8 mm
Da	81 mm
db	53 mm
ra max.	1,5 mm
da	55 mm
Db	89 mm
Weight	1,03 Kg
Basic dynamic load rating (C)	87,5 kN
Basic static load rating (C0)	97 kN
(Grease) Lubrication Speed	3600 r/min
(Oil) Lubrication Speed	5300 r/min
Calculation factor (e)	0,74
Calculation factor (Y0)	0,45



Timken MANUFACTURING (THAILAND)CO.,LTD.

LangID	1
ALP23	0
outer r	0.8
ALP22	30
D_	95.25
ALP21	52
SHOG_yobi	53150R/53375R
RAr	98.508
inner r	1.5
GRS rpm	3600
D_b	89
D_a	81
DE_	78.337
SLR	18
Prod_Type3	TRBSR_ID_A
BETA_	4
ALPHA_	26.25
SDM_	67.784
DA1	13.741
DA2	11.259
hidYobi	53150/53375
Y1	0.81
B_	28.301
Oil rpm	5300
hidTable	ecat_NSTPRI
Y0	0.45
inner ra	1.5
outer rb	0.8
C0	97
CUP	0.365
e	0.74
DA_	12.518



Timken MANUFACTURING (THAILAND)CO.,LTD.

BET21	8
BET22	0
BET23	0
Z_	14
C_	20.638
yobi	53150/53375
KBRG	3161
CONE	0.665
DI_	56.004