



Timken MANUFACTURING (THAILAND)CO.,LTD.



120 mm x 180 mm x 28 mm NSK 6024 deep groove ball bearings

Bearing No. 6024

6024 Bearing 2D drawings and 3D CAD models

Size	120x180x28 mm
Bore Diameter	120 mm
Outer Diameter	180 mm
Width	28 mm
d	120 mm
D	180 mm
B	28 mm
C	28 mm
r min.	2 mm
da min.	129 mm
da max	134,5 mm
Da max.	171 mm
ra max.	2 mm
Weight	2,08 Kg
Basic dynamic load rating (C)	88 kN
Basic static load rating (C0)	80 kN
(Grease) Lubrication Speed	3 600 r/min
(Oil) Lubrication Speed	4 300 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	2.1
EAN	0029176013409
Product Group	B00308



Timken MANUFACTURING (THAILAND)CO.,LTD.

Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	120MM Bore; 180MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6024
Weight / LBS	2.09
Bore	4.724 Inch 120 Millimeter
Outside Diameter	7.087 Inch 180 Millimeter
Outer Race Width	1.102 Inch 28 Millimeter
bore diameter:	120 mm
static load capacity:	80000 N
outside diameter:	180 mm
precision rating:	ABEC 1 (ISO Class Normal)
overall width:	28 mm



Timken MANUFACTURING (THAILAND)CO.,LTD.

finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
internal clearance:	C0
maximum rpm:	4300 RPM
operating temperature range:	Maximum of +250 ° F
series:	60
dynamic load capacity:	88000 N
SRI	9.86
hidYobi	6024
LangID	1
D_	180
SREX	0.04
B_	28
da min	129
hidTable	ecat_NSRDGB
Oil rpm	4300
SRE	9.86
mass	2.08
GRS rpm	3600
ra	2
SRIX	0.04
D_a	171
SRIN	-0.04
C0	80
fo	15.7
SREN	-0.04
DE_	169.05



Timken MANUFACTURING (THAILAND)CO.,LTD.

Prod_Type3	DGBB_SR_OT
DA_	19.05
bomp	0
Z_	14
yobi	6024
C_conv	88000
ALPHA_	0
SDM_	150
r	2
KBRG	6101
SBRG	10
DI_	130.95