



8 mm x 19 mm x 6 mm SKF W 619/8 deep groove ball bearings

Bearing No. W 619/8

W 619/8 Bearing 2D drawings and 3D CAD models

Size	19x8x6 mm
Bore Diameter	19 mm
Outer Diameter	8 mm
Width	6 mm
d	8 mm
D	19 mm
B	6 mm
d ₂	9.8 mm
D ₂	16.66 mm
r _{1,2} - min.	0.3 mm
d _a - min.	9.7 mm
D _a - max.	17 mm
r _a - max.	0.3 mm
Basic dynamic load rating - C	1.2 kN
Basic static load rating - C ₀	0.455 kN
Fatigue load limit - P _u	0.02 kN
Reference speed	85000 r/min
Limiting speed	53000 r/min
Calculation factor - k _r	0.025
Calculation factor - f ₀	6.6
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



Timken MANUFACTURING (THAILAND)CO.,LTD.

Weight / Kilogram	0.006
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	8MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainless Steel C
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Weight / LBS	0.0139
Bore	0.315 Inch 8 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter
Outside Diameter	0.748 Inch 19 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d ₂	9.8 mm
D ₂	16.66 mm
r _{1,2} min.	0.3 mm



Timken MANUFACTURING (THAILAND)CO.,LTD.

d_a min.	9.7 mm
D_a max.	17 mm
r_a max.	0.3 mm
Basic dynamic load rating C	1.25 kN
Basic static load rating C_0	0.455 kN
Fatigue load limit P_u	0.02 kN
Calculation factor k_r	0.025
Calculation factor f_0	6.6
Mass bearing	0.0061 kg